

BASIC TELECOMMUNICATIONS: STUDENT GUIDE

TABLE OF CONTENTS

Course Description	xiii
ComputerPREP Courseware.....	xiv
Course Objectives	xv
Classroom Setup	xviii
Lesson 1: Overview	1-1
Pre-Assessment Questions.....	1-2
The Telecommunications Industry	1-3
Terms and Technology.....	1-6
Regulation and Public Policy.....	1-11
Technical Platform.....	1-19
The International Perspective.....	1-21
Lesson Summary	1-24
Lesson 1 Review	1-26
Lesson 2: Customer Premise Equipment (CPE)	2-1
Pre-Assessment Questions.....	2-2
Station Sets	2-3
Key Systems	2-11
Private Branch Exchange (PBX)	2-16
Centrex—Virtual PBX	2-24
Lesson Summary	2-25
Lesson 2 Review	2-27
Lesson 3: Services	3-1
Pre-Assessment Questions.....	3-2
Introduction	3-3
Service Basics	3-11
Line and Trunk Features	3-16
Dedicated Services.....	3-21
Service Providers	3-24
Specialized Services.....	3-26
Lesson Summary	3-31
Lesson 3 Review	3-34
Lesson 4: Analog Concepts	4-1
Pre-Assessment Questions.....	4-2
The Network	4-3

The Voice Signal	4-4
Transmission Variables	4-5
Multiplexing	4-7
FDM	4-8
Lesson Summary	4-11
Lesson 4 Review	4-13

Lesson 5: Digital Concepts **5-1**

Pre-Assessment Questions.....	5-2
Digital Signals	5-3
Advantages of Digital Technology	5-4
Digital Transmission.....	5-5
Pulse Code Modulation	5-7
Digital Voice Transport	5-12
Optical Standards.....	5-14
Digital Loop Carriers.....	5-17
Lesson Summary	5-18
Lesson 5 Review	5-19

Lesson 6: Networks **6-1**

Pre-Assessment Questions.....	6-2
Telecommunications Networks.....	6-3
The Flexibility of Computer Technology.....	6-4
Current Network Structure	6-5
The Exchange/Central Office	6-9
Cellular Networks	6-12
Internet Telephony	6-14
Lesson Summary	6-19
Lesson 6 Review	6-21

Lesson 7: Transmission **7-1**

Pre-Assessment Questions.....	7-2
A Simple Transmission Network	7-3
What Are the Transmission Media?.....	7-4
Two-Wire Analog Media	7-8
Multicircuit Media and Systems.....	7-12
Lesson Summary	7-18
Lesson 7 Review	7-20

Lesson 8: Signaling **8-1**

Pre-Assessment Questions.....	8-2
Basic Types of Signaling	8-3
Supervisory Signaling.....	8-5
Start-Dial Signals	8-8
Address Signaling.....	8-8
Incoming Call Indication.....	8-10
Call Progress Tones and Miscellaneous Signals.....	8-11
Common Channel Signaling	8-12
Signaling System 7 (SS7)	8-14
Identifying the Signaling Interface.....	8-21
Lesson Summary	8-25

Lesson 8 Review	8-27
-----------------------	------

Lesson 9: Switching **9-1**

Pre-Assessment Questions.....	9-2
Introduction to Switching	9-3
Analog Switches	9-5
Digital Switches.....	9-6
Time-Division Switching	9-7
Space-Division Switching.....	9-9
CO Digital Switches.....	9-10
Optical Signal Switching.....	9-14
Lesson Summary.....	9-14
Lesson 9 Review	9-16

Lesson 10: Application Analysis **10-1**

Pre-Assessment Questions.....	10-2
Determination of Applications.....	10-3
Determination of Quantities.....	10-15
Lesson Summary.....	10-18
Lesson 10 Review	10-20

Glossary **Glossary-1**

Index **Index-1**

Supplemental CD-ROM Contents **Supplemental CD-ROM Contents-1**

List of Figures

Figure 1-1: IP phones, cable modem, and cell phones support voice, fax, and data.....	1-3
Figure 1-2: Growth in telephony since 1980.....	1-4
Figure 1-3: LECs share telecommunication markets with competitors.....	1-5
Figure 1-4: Telecommunications revenue distribution over time.....	1-6
Figure 1-5: Demarc is connection point between CPE and PSTN	1-7
Figure 1-6: Demarc is often housed in equipment room	1-7
Figure 1-7: Wire center houses switch that is connected to all other switches	1-9
Figure 1-8: Access connects CPE to network.....	1-10
Figure 1-9: The FCC regulates interstate communications	1-11
Figure 1-10: Standards organizations	1-12
Figure 1-11: Current state of telecommunications industry regulation	1-13
Figure 1-12: Telecommunications industry monopolization and demonopolization	1-14
Figure 1-13: Telecommunications industry regulation before 1980s.....	1-16
Figure 1-14: Telecommunications industry regulation -- 1990s (United States)	1-17
Figure 1-15: Telecommunications industry regulation — 2000s	1-18
Figure 1-16: Early development of telecommunications technology	1-19
Figure 1-17: Stored program control switch reduced telephony costs	1-20
Figure 1-18: Mobile telephones and Web browsers changed telecommunications	1-20
Figure 2-1: Station sets are made in many varieties	2-3
Figure 2-2: Station set functions.....	2-4
Figure 2-3: Single line and multiline analog sets	2-5
Figure 2-4: Analog signaling techniques.....	2-6
Figure 2-5: Touchtone signaling.....	2-7
Figure 2-6: Supervisory signaling.....	2-8

Figure 2-7: A digital set has more than one pair of wires	2-8
Figure 2-8: Digital sets use message-oriented and stimulus signaling	2-9
Figure 2-9: Advanced station set features	2-10
Figure 2-10: Wireless sets communicate through antennas.....	2-11
Figure 2-11: Key systems allow users to share lines.....	2-12
Figure 2-12: Key system inbound features	2-13
Figure 2-13: DNIS identifies the number originally dialed by the caller.....	2-14
Figure 2-14: Key system outbound features	2-15
Figure 2-15: Intercom calling features	2-16
Figure 2-16: Key systems versus PBXs	2-16
Figure 2-17: Outbound call functionality of PBX systems.....	2-17
Figure 2-18: Inbound call functionality of PBX systems	2-18
Figure 2-19: Intra-business features of PBX systems	2-19
Figure 2-20: OPX and DISA are PBX features used by off-premise employees.....	2-20
Figure 2-21: Automatic call distributor (ACD)	2-20
Figure 2-22: PBX system with ACD.....	2-21
Figure 2-23: PBX administrative and maintenance capabilities	2-22
Figure 2-24: Systems associated with PBX systems	2-22
Figure 2-25: Centrex is provided by an LEC or IXC	2-24
Figure 3-1: Types of telecommunications services	3-3
Figure 3-2: Call billing regions.....	3-4
Figure 3-3: Local call billing.....	3-4
Figure 3-4: Billing boundaries	3-5
Figure 3-5: San Francisco local calling area.....	3-6
Figure 3-6: Local calling area for Sunnyvale.....	3-7
Figure 3-7: California LATA map.....	3-7
Figure 3-8: Long-distance call billing	3-7
Figure 3-9: Internal carrier billing.....	3-8
Figure 3-10: Analog business lines	3-11
Figure 3-11: Key systems use analog lines to connect to network.....	3-12
Figure 3-12: 2-way combo trunks can be analog or digital	3-12
Figure 3-13: 2-way combo and outdial trunks.....	3-13
Figure 3-14: DID trunks allow direct calls to receiving station.....	3-13
Figure 3-15: Dedicated access using T1 system	3-14
Figure 3-16: 2-way DID using dedicated access	3-15
Figure 3-17: 2-way DID with long-distance service.....	3-15
Figure 3-18: Integrated T1 reduces the number of trunks required	3-16
Figure 3-19: CPE features.....	3-17
Figure 3-20: Sequential hunting	3-19
Figure 3-21: Circular hunting.....	3-19
Figure 3-22: Remote call forwarding	3-20
Figure 3-23: Features available on trunks.....	3-20
Figure 3-24: Non-switched services are dedicated services	3-21
Figure 3-25: Pricing depends on service type, bandwidth and distance.....	3-21
Figure 3-26: Many small businesses use traditional switched access	3-24
Figure 3-27: PBXs use dedicated access	3-24
Figure 3-28: Integrated communications providers can provide all services.....	3-25
Figure 3-29: Matrix of services available from providers	3-26
Figure 3-30: Specialized services	3-26
Figure 3-31: ISDN and switched 56 connections	3-29
Figure 3-32: Service provider application project.....	3-31
Figure 4-1: Switching refers to the routing of a call.....	4-3
Figure 4-2: Signaling involves call setup information	4-3
Figure 4-3: Transmission transmits voice and data point-to-point.....	4-3
Figure 4-4: Sound is produced by moving air.....	4-4
Figure 4-5: Transduction is the conversion of energy	4-4
Figure 4-6: An analog signal can be charted as a sine wave	4-4

Figure 4-7: Frequency is the number of cycles completed in a second	4-5
Figure 4-8: A string can carry sound.....	4-5
Figure 4-9: The effect of attenuation on frequency	4-6
Figure 4-10: The effect of attenuation on frequency in loaded cable.....	4-6
Figure 4-11: Electrical noise is caused by nearby electrical interference	4-7
Figure 4-12: Full-duplex transmission	4-7
Figure 4-13: Open wire line, radio and coax carry multiplexed signals	4-8
Figure 4-14: Frequency-division multiplexing (FDM)	4-8
Figure 4-15: Modulation	4-9
Figure 4-16: Signal modulation.....	4-9
Figure 4-17: The bandpass filter removes the extra sideband and carrier	4-10
Figure 4-18: Channel bank output.....	4-10
Figure 4-19: Channel capacity of L carriers.....	4-10
Figure 4-20: Factors affecting noise in analog systems.....	4-11
Figure 5-1: Digital signals versus analog signals	5-3
Figure 5-2: Analog signals are electrical energy	5-3
Figure 5-3: Digital signals represent the original signal indirectly.....	5-3
Figure 5-4: Analog bandwidth is measured in frequency range.....	5-3
Figure 5-5: Digital bandwidth is measured in bits per second	5-4
Figure 5-6: Regenerators restore attenuated digital signals	5-4
Figure 5-7: Noise is amplified with analog signal.....	5-4
Figure 5-8: Digital signals are resistant to crosstalk.....	5-5
Figure 5-9: Digital circuitry has become more affordable.....	5-5
Figure 5-10: Backward compatibility requires signal conversion	5-6
Figure 5-11: Codecs perform analog/digital conversions	5-6
Figure 5-12: Codecs are found in many types of equipment	5-7
Figure 5-13: Codecs use many methods of analog-to-digital conversion	5-8
Figure 5-14: Pulse amplitude modulation samples 8,000 times per second	5-8
Figure 5-15: PAM's output—series of pulses	5-9
Figure 5-16: DPCM focuses on difference between samples.....	5-10
Figure 5-17: ADPCM addresses DPCM's weaknesses.....	5-11
Figure 5-18: Delta modulation records direction of change in samples	5-11
Figure 5-19: DS0 is standard for single PCM voice channel.....	5-12
Figure 5-20: DS1 frame is composed of 24 DS0s and one framing bit.....	5-13
Figure 5-21: Channelized versus non-channelized T1	5-13
Figure 5-22: DS0 digital hierarchy for electronic media.....	5-14
Figure 5-23: Optical transmission includes source, medium and receiver	5-14
Figure 5-24: Optical carrier standards	5-14
Figure 5-25: Twisted pair is used for distances up to 15,000 feet from CO	5-17
Figure 6-1: IXC POPs in rural areas carry signals to remote switches.....	6-3
Figure 6-2: Metropolitan areas require complex networks	6-3
Figure 6-3: Complex networks offer multiple management schemes.....	6-4
Figure 6-4: Missouri LATA map	6-5
Figure 6-5: LATAs contain many COs and several exchanges	6-5
Figure 6-6: IXC POPs can provide IXC access within LATA.....	6-6
Figure 6-7: Rural LATA using wire center.....	6-6
Figure 6-8: IXC A has direct connection with all ILECs	6-7
Figure 6-9: IXC B has connection with ILECs it uses frequently.....	6-7
Figure 6-10: CLEC A and CLEC B are both directly connected to IXC C	6-8
Figure 6-11: Missouri LATA map and area codes	6-8
Figure 6-12: Metropolitan wire center	6-10
Figure 6-13: CLEC circuit switch with digital crossconnect and multiplexers	6-11
Figure 6-14: Mesh configuration used in areas of heavy traffic.....	6-11
Figure 6-15: Star configuration is used in less dense areas.....	6-12
Figure 6-16: Cellular service is provided within MSAs.....	6-12
Figure 6-17: MTSOs route calls to best site to maximize signal strength.....	6-13
Figure 6-18: Roaming occurs when cell phone is outside its home area.....	6-13

Figure 6-19: Generations of cellular technology	6-14
Figure 6-20: VoIP is Internet transmission of voice and video	6-15
Figure 6-21: PSTN versus Internet	6-16
Figure 6-22: Gateways are required for calls between PCs and phones	6-17
Figure 6-23: VoIP using private Internet or intranet	6-18
Figure 6-24: Cable providers now offer voice services	6-19
Figure 7-1: Typical analog phone call.....	7-3
Figure 7-2: All calls are transmitted to CO for switching	7-3
Figure 7-3: Calls are transmitted over trunk to IXC POP	7-3
Figure 7-4: Call may be transmitted to another CO	7-4
Figure 7-5: Intra-office calls stay within same wire center	7-4
Figure 7-6: Telephone poles and cable were common transmission media	7-4
Figure 7-7: Types of transmission media.....	7-5
Figure 7-8: Full-duplex transmission	7-5
Figure 7-9: Carrier system used to connect PBX with CO.....	7-6
Figure 7-10: T carrier systems do not require digital/analog conversion.....	7-6
Figure 7-11: Interoffice trunks are carrier systems.....	7-6
Figure 7-12: Many different access and transport options exist.....	7-7
Figure 7-13: Types of access systems.....	7-7
Figure 7-14: Types of transport systems	7-8
Figure 7-15: Most analog residential circuits are two-wire circuits	7-8
Figure 7-16: Every residence must be connected to access network	7-8
Figure 7-17: DSL can use data-over-voice or pure data	7-9
Figure 7-18: Carriers use smart jack to terminate T1 circuit	7-10
Figure 7-19: T1 carrier transmits 24 8-bit DS0 signals and one framing bit	7-10
Figure 7-20: D4 superframe framing bit pattern.....	7-10
Figure 7-21: Extended superframe (ESF) requires 24 frames.....	7-11
Figure 7-22: T1 can be multiplexed.....	7-13
Figure 7-23: Electrical carrier standards.....	7-13
Figure 7-24: SONET optical carrier standards.....	7-14
Figure 7-25: One OC1 carries 28 T1s.....	7-14
Figure 7-26: Add/drop multiplexers do not require multiplexing	7-14
Figure 7-27: Digital crossconnect system (DCS) mapping and test access ports.....	7-15
Figure 7-28: SONET management includes bits for section, line and path.....	7-15
Figure 7-29: Alternate mark inversion (AMI).....	7-17
Figure 7-30: 2-binary, 1 quaternary (2B1Q)	7-17
Figure 7-31: Quadrature amplitude modulation (QAM)	7-18
Figure 8-1: Subscriber signaling, or line-side signaling	8-3
Figure 8-2: Interswitch signaling, or trunk-side signaling.....	8-3
Figure 8-3: Subscriber signaling uses DC signaling	8-3
Figure 8-4: In-band signaling.....	8-4
Figure 8-5: Out-of-band signaling	8-4
Figure 8-6: Common channel signaling.....	8-5
Figure 8-7: Types of supervisory signaling in UNI.....	8-6
Figure 8-8: Loop-reverse battery supervision.....	8-7
Figure 8-9: Out-of-band supervision used with ISDN or CCS lines	8-7
Figure 8-10: Start dial signaling	8-8
Figure 8-11: U.S. address signaling	8-9
Figure 8-12: DTMF, rotary dial and MF signaling	8-10
Figure 8-13: Incoming call signaling varies based on trunk type	8-11
Figure 8-14: In-band call signals	8-11
Figure 8-15: Call setup and transmission using in-band signaling.....	8-13
Figure 8-16: CCS network structure	8-13
Figure 8-17: Many different links are used between CCS components	8-15
Figure 8-18: Switches and signaling make SS7 services possible.....	8-15
Figure 8-19: SS7 signaling for direct long-distance call	8-16
Figure 8-20: Redirected call using SS7 signaling.....	8-17

Figure 8-21: Calling name retrieval in SS7 network	8-18
Figure 8-22: Complete call using in-band signaling.....	8-19
Figure 8-23: Complete call using out-of-band signaling.....	8-20
Figure 8-24: Loop-start signaling is provided from the line side of the switch	8-21
Figure 8-25: DID connections are on trunk side of telco switch	8-22
Figure 8-26: PBXs connected with tie trunks	8-22
Figure 8-27: ISDN PRI has more powerful signal than ISDN BRI	8-22
Figure 8-28: SS7 is used between switches	8-23
Figure 9-1: Concentration, distribution and expansion are switching functions.....	9-3
Figure 9-2: Switching functions	9-4
Figure 9-3: Operations, administration, maintenance and provisioning	9-4
Figure 9-4: Switching structure	9-5
Figure 9-5: Step-by-step switching.....	9-5
Figure 9-6: Crosspoint switches—several individual switches arranged in matrix	9-6
Figure 9-7: Time-division multiplexing (TDM).....	9-7
Figure 9-8: Time-division switching rearranges time slots within frames	9-7
Figure 9-9: Reordering time slots requires control logic, buffer and counter	9-8
Figure 9-10: Control logic determines unloading order of time slots	9-8
Figure 9-11: Time-division switching is useful when inputs and outputs are equal	9-9
Figure 9-12: Space-division switching is useful when inputs and outputs differ	9-9
Figure 9-13: Space-division switching moves DS0s or DS1s.....	9-9
Figure 9-14: Logic gates are closed at intersecting points.....	9-10
Figure 9-15: Time-division versus space-division switching.....	9-10
Figure 9-16: Switches have control elements and switching fabric	9-11
Figure 9-17: Each space-switching matrix is one stage	9-11
Figure 9-18: Time-space-time (TST) switch.....	9-12
Figure 9-19: Switch configuration using time slot 4	9-13
Figure 10-1: Planning	10-3
Figure 10-2: Business needs.....	10-3
Figure 10-3: Discovery process—interviews.....	10-4
Figure 10-4: Considerations for discovery process.....	10-4
Figure 10-5: Interview goals.....	10-5
Figure 10-6: Discussion areas for discovery process.....	10-6
Figure 10-7: System administration concerns	10-6
Figure 10-8: Information access factors	10-7
Figure 10-9: Direct inward dialing (DID)	10-8
Figure 10-10: Inbound access to fax	10-8
Figure 10-11: Internet access considerations	10-9
Figure 10-12: Conferencing needs.....	10-9
Figure 10-13: Connectivity needs.....	10-10
Figure 10-14: Benefits of similar systems.....	10-10
Figure 10-15: Remote workers' needs	10-11
Figure 10-16: Telecommuters' needs.....	10-12
Figure 10-17: Security concerns	10-12
Figure 10-18: Business continuity	10-13
Figure 10-19: Protection of information.....	10-13
Figure 10-20: Call center considerations.....	10-14
Figure 10-21: Information flow matrix	10-15
Figure 10-22: Voice circuit needs.....	10-16
Figure 10-23: Busy hour variations	10-16
Figure 10-24: Service model	10-17
Figure 10-25: Service criteria.....	10-18

List of Tables

Table 1-1: Telephony growth since 1980	1-4
Table 1-2: Additional telephony authorities.....	1-23

Table 3-1: Sunnyvale local calling areas.....	3-6
Table 3-2: Telephone code changes.....	3-9
Table 3-3: Country codes.....	3-10
Table 3-4: First four levels of DSH and T-carrier equivalents.....	3-23
Table 3-5: E-carrier speeds.....	3-23
Table 5-1: Predictive codec types.....	5-12
Table 5-2: ANSI-mandated rates for SONET.....	5-16
Table 5-3: ITU-specified rates for SDH.....	5-16
Table 8-1: Common signaling interfaces.....	8-24
Table 9-1: TST switch calls.....	9-12